



BALANCE SCALE

Type	Range	Calibration
MP60K-1	Capacity(kg):60, Readability(g):1, Repeatability(\leq g): ± 1 , Linearity(\leq g): ± 2	External
MP100K-1	Capacity(kg):100, Readability(g):1, Repeatability(\leq g): ± 1 , Linearity(\leq g): ± 2	External
MP60K	Capacity(kg):60, Readability(g):5, Repeatability(\leq g): ± 5 , Linearity(\leq g): ± 10	External
MP100K	Capacity(kg):100, Readability(g):5, Repeatability(\leq g): ± 5 , Linearity(\leq g): ± 10	External
MP150K	Capacity(kg):150, Readability(g):10, Repeatability(\leq g): ± 10 , Linearity(\leq g): ± 20	External
MP200K	Capacity(kg):200, Readability(g):10, Repeatability(\leq g): ± 10 , Linearity(\leq g): ± 20	External
MP300K	Capacity(kg):300, Readability(g):20, Repeatability(\leq g): ± 20 , Linearity(\leq g): ± 40	External



Characteristic:

1. Large screen backlight LCD display
2. Built-in rechargeable spare battery
3. Built-in RS232 interface unit conversion



MODERN
INSTRUMENTS



No 18, Xuwang Road, QingPu District Shanghai, China



+86 2159884839



info@moderner.com