



Balance (1/100 Precision)

- High precision sensor
- Ultra-clear LCD backlight display screen
- Front horizontal bubble adjustment, intuitive and convenient
- The stability time and reaction speed of weighing results are adjustable, and the reaction time is less than 2s.
- A variety of weighing unit conversion functions
- Standard RS232 interface
- Power supply:110V-240V, 50HZ/60HZ
- Optional functions: USB storage function, printer, second display screen, checkweighing alarm lamp, lower hook weighing device,DC12V 1000mA battery and other accessories.



Disc plate



Square plate

Balance (1/100) — Disc Plate

Type	Maximum range (g)	Readability (g)	Repeatability (\leq g)	linear error (\leq g)	Scale size (mm)	Functional characteristics
JA1202	120	0.01	± 0.01	± 0.02	$\phi 115$	External
JA2202	220	0.01	± 0.01	± 0.02	$\phi 115$	External
JA3202	320	0.01	± 0.01	± 0.02	$\phi 115$	External
JA5202	520	0.01	± 0.01	± 0.02	$\phi 115$	External
JA6202	620	0.01	± 0.01	± 0.02	$\phi 115$	External
JA1202	1000	0.01	± 0.01	± 0.02	$\phi 115$	External

Balance (1/100) — Square Plate

Type	Maximum range (g)	Readability (g)	Repeatability (\leq g)	linear error (\leq g)	Scale size (mm)	Functional characteristics
JA12002	1200	0.01	± 0.01	± 0.02	192×171	External
JA22002	2200	0.01	± 0.01	± 0.02	192×171	External
JA32002	3200	0.01	± 0.01	± 0.02	192×171	External
JA52002	5200	0.01	± 0.01	± 0.02	192×171	External
JA62002	6200	0.01	± 0.01	± 0.02	192×171	External



**MODERN
INSTRUMENTS**



No 18, Xuwang Road, QingPu District Shanghai, China



+86 2159884839



info@moderner.com